



O' Tannenbaum 2.5 – Product Specification



M 1:200



HodgePodge – A variety of study and durable sport and play elements

HodgePodge is a clever and versatile combination of play equipment and climbing structures that can be used anywhere and for numerous activities. Climbing trees, a Wasp's nest, Volleyball nets for sporting activities, cable rides for fun and excitement.

O' Tannenbaum 2.5 – At a glance.

Product Family:	HodgePodge	Number of Foundations:	1 pc.
Item Number:	90.340.045	Concrete Volume C20/C25:	1.2 m³ (42.4 ft³)
Children's Age:	3+	Number of skilled installers required:	3
Fall Height (DIN EN 1176):	0.40 m (1'-4")	Installation Time without foundation:	6 hours
Length x Width x Height:	2.1 m x 2.1 m x 2.5 m (6'-9" x 6'-9" x 8'-3")	Dimensions of largest part:	Ø 0.1 m x 3.4 m (0'-4" x 11'-2")
Protective Surfacing Area (DIN EN 1176):	5.1 m x 5.1 m	Weight of heaviest part:	75 kg (165.3 lbs)
Protective Surfacing Area (ASTM 1487):	5.7 m x 5.7 m (18'-9" x 18'-9")	Shipping Volume:	1.7 m³ (60.0 ft³)
Minimum space required DIN EN 1176:	20.0 m²	Spare part guarantee:	Lifelong
Minimum space required ASTM 1487:	25.6 m² (275.6 sf)	Certificate according to EN 1176:	No.: Z2.16.01.10256.257 TÜV Product Service

Technical Data.

The following text can also be used for tenders.

Central mast:

Steel post 133 mm (5 1/4"), wall thickness 6.3mm (1/4"), anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process.

Mast node:

Framework-aluminum ball connector; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; with inlying net tensioning system, secured with a durable EPDM-cap.

Rubber membrane:

Comprised of durable, vandal-resistant conveyor belt material.

Ropes:

U-Rope®-round strand ropes with galvanized and covered wires: external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene); rope-diameter Ø 16 mm (5/8").

Outer rings:

Bended Framework-steel pipes, Ø 48.3 mm (1 7/8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process.

Netting and suspension ropes:

rope crossing points localized by durable, drop forged aluminium-ballknots (no plastic).




Berliner
 Berliner Seilfabrik GmbH & Co.
 Lengeder Straße 2/4
 D-13407 Berlin

Tel. +49.(0)30.41 47 24-0
 Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com
 www.berliner-seilfabrik.com