




SCALE 1:40



LTD "KENGURU PRO"
 Address: Ezera street 21-28, Riga, Latvia, LV-1034
 VAT Reg. No. 40103750152
 Bank: A/S DNB bank, SWIFT: RIKOLV2X,
 Bank Account: LV65RIKO0002930161161
 e-mail: info@kengurupro.eu
 www.kengurupro.eu

K-014

Double pull-up bar



Consists of three vertical backup columns at the height of 2600 mm -2 pieces, 2300 mm -1 piece and horizontal crossbars with the length of 1200 mm. All elements of the construction are fixed with collars at the height that corresponds to the demands of the Client. Weight 102.5 kg

Installation instructions:

- Choose a suitable underground for the unit (see page 2, table 2)!
- Prepare the construction pit with a drilling machine or other devices.
- Before pouring the concrete all structures elements must be leveled and fixed.
- Complex elements must be fixed and bolted together with metal clamps.
- Ready-made C25 concrete should be used.
- Crossbars installation height can be changed according to customer's wishes.
- Approximately 0,15m³ concrete is needed for each spot foundation.
- Under the structures we recommend to install absorbing rubber cover.

The size of the hole for the foundation is depending on the consistency of the ground. The dimensions mentioned above are applicable for normal conditions with firm ground. If the ground is extremely soft, a much bigger foundation is needed. Use only appropriate material and follow the installation instructions closely!!!

Foundation plan and area of movement of the K-014 Double pull-up bar				Technical information	
Foundation when using Shock absorbing underground (synthetic – rubber granulates)		Beveling of foundation when using loose filling material		width:	108 mm
				height:	2650 mm
				length:	2724 mm
H3	Drop height	H3	Drop height	largest part:	3350 mm
40 mm	> 1.2.....1.4 m	20 cm	< 1.0 m	weight:	102.5 kg
50 mm	> 1.5.....1.7 m	30 cm	< 2.0 m	floor space required:	4108 x 6724 mm
60 mm	> 1.8.....2.0 m	40 cm	< 3.0 m	pipe measurements:	diameter: 108 mm
70 mm	> 2.1.....2.5 m				wall thickness: 3.2 mm
					33.7 mm
				metal parts:	steel, galvanized, powder coated RAL 7016 (anthracite grey)
				metal clamps:	aluminium, powder coated, RAL 2004 (pure orange)
				bolts for metal clamps:	stainless steel, Pin Hex Button Head Security Screws M10
				max. free fall height:	< 2400 mm
				user age:	children under 14 years only under surveillance of parents
				maximum user weight:	130 kg
				certificates:	TÜV Rheinland InterCert Kft.

