

CatTail.01 – Product Specification



Cat Tail.01

The full-size Cat Tail.01 sways to and fro all the time... hey, it's a cat tail!
The Cat Tail has a body and a stem made out of stainless steel. The curved stem and the bi-colored HDPE-platform turns a piece of play equipment into an eye-catcher for all public places in town.



Cat Tail.01 – at a glance.

Product Family:	Playpoints	Number of Foundations:	1 pc.
Item Number:	90.260.201	Concrete Volume C20/C25:	0.5 m³ (18 ft³)
Children's Age:	5+	Number of skilled installers required:	2
Fall Height (DIN EN 1176):	0.4 m (1'-4")	Installation Time without foundation:	2 hours
Length x Width x Height:	0.7 m x 0.4 m x 2.5 m (2'-4" x 1'-4" x 8'-3")	Dimensions of largest part:	0.7 m x 0.4 m x 2.9 m (2'-4" x 1'-4" x 9'-7")
Protective Surfacing Area (DIN EN 1176):	3.6 m x 3.6 m	Weight of the heaviest part:	55 kg (122 lbs)
Protective Surfacing Area (ASTM 1487):	4.3 m x 4.3 m (14'-2" x 14'-2")	Shipping Volume:	1.7 m³ (60.1 ft³)
Minimum space required DIN EN 1176:	10.2 m²	Shipping Weight:	85 kg (188 lbs)
Minimum space required ASTM 1487:	14.3 m² (154 ft²)	Spare part guarantee:	Lifelong
		Certificate according to DIN EN 1176:	No.: Z2 15 07 10256 237 TÜV Product Service

Technical Data.

The following text can also be used for tenders.

Base plate:

Stainless steel plate Ø 320 mm (1'-1"), covered with HDPE panels, 19 mm (3/4") thickness

Tubes:

Stainless steel tubes, Ø 48.3 & 40,0 mm (1'-7" & 1'-4"), slightly bended, connected to an Frameworx®-aluminum ball connector; Ø 200 mm (8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; securely closed with durable EPDM-cap

Luffing mechanism:

Fully encapsulated rubber-metal-bearing integrated in stainless steel foundation tube

Covering:

Antiskid HDPE panels, 19 mm (3/4"), bolted on the base plate


Berliner
Berliner Seilfabrik GmbH & Co.
Lengeder Straße 2/4
D-13407 Berlin

Tel. +49.(0)30.41 47 24-0
Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com
www.berliner-seilfabrik.com

