

Articolo /item

Codice / Code

COLUMN RACE SMART

Finitura /Finishing

ANTICORODAL PAINTED ALUMINIUM



Maintenance and charging station for e-bikes, equipped with:

- 1 Phillips screwdriver
- 1 slotted screwdriver
- 1 0/22 mm roller spanner
- 2 tyre levers
- 1 fixed spanner 14/15 mm
- 1 fixed spanner 12/13 mm
- 1 set of Allen keys 2.5-10 mm

There are two flush-mounted IP54 SCHUKO sockets connected to a magnetothermal differential switch Id 0.003mA.

The two sockets have a rated current of 16 A, the rated voltage is 230 V and the rated frequency is 50Hz.

The rated current of the circuit breaker is 25/22 A.

The structure is complete with a tyre inflation pump with a universal connection, complete with pressure indicator and a pumping capacity of up to 8 bar.

The column is delivered already wired with a three-pole FG7 3X2.5 cable about two metres long for outdoor connection.

It is available in olive green, air force blue and urban grey, and versions with 1 or 2 built-in bike racks are available on request.

The structure is made of anticorodal aluminium and all hardware is stainless steel.

TECHINICAL INFORMATION

Dimensions: L. 590 x 440 mm

Height: 1504 mm

Approx.

Weight: 18.5/20 kg



NOTE

Rev. 11/2022