

1. Applications

EUROFLEX® Balls are used as seating and communication islands in playing areas and also as playing components.

EUROFLEX® Balls are manufactured by an environment-friendly process and can be recycled as process raw material at the end of their service life.

2. Material

Rubber granulate: granulated recycled rubber
Binding agent: MDI polyurethane

3. Characteristics

Colour: red, green, grey or black
(minor colour variation possible)
Surface: smooth with open pores

4. Dimensions / Tolerances

Diameter: approx. 345 mm, 500 mm, 695 mm
Weight: approx. 18,3 kg, 56,0 kg, 150,4 kg
Tolerances: +/- 0,8%
Dimension steel anchors: Ø 42,8 mm, length approx. 750 mm

5. Material Ball with EPDM topping

Rubber granulate: granulated recycled rubber
Binding agent: MDI polyurethane
Topping: Coloured EPDM rubber granulate



All information without guarantee, subject to change. The Data Sheet is not subject to any change service.
Each current and valid from can be recalled at www.kraiburg-relastec.com/euroflex

6. Characteristics

Surface: minor colour variation possible
smooth with open pores

7. Dimensions / Tolerances

Diameter: approx. 345, 500, 695 mm
Weight: approx. 20,4 kg, 60,0 kg, 166,0 kg
Tolerances: +/- 0,8 %
Dimension steel anchors: Ø 42,8 mm, length approx. 750 mm

8. Test Data

Production facility inspection
EN 1176-1:2017

Migration of certain elements: in accordance with DIN EN 71-3

Fire resistance: E (DIN EN 13501-1, 2010)

Chemical resistance: conditionally resistant to acids and bases

9. Installation

Install EUROFLEX® Ball by inserting their steel anchors.